

## TYPE PV

### Panel Ventilator

- Suitable for roof pitches of 15 degrees upwards
- Compatible with fascia and soffit ventilators
- Easy-fit
- Excellent free airflow



#### Solution


In pitched roof applications, the Type PV Panel Ventilator fits between the roof trusses and maintains a defined airflow path between the underside of roofing felt and the roof insulation. The function of the Type PV is to receive air that enters and exists via a fascia or soffit ventilator. Air is channelled through the body of the ventilator via apertures within the bottom and top upstand edges.

#### Bill of Quantity / Specification Wording

##### 900 Eaves Ventilators

Type PV Panel Ventilator by Cavity Trays of Yeovil Somerset BA22 8HU (01935 474769). Colour black. Secure to roof timber along all eaves. Metres run \_\_\_\_\_.


<b>Product name</b>	Type PV Panel Ventilator
<b>Size (3) to suit truss centres 400/450/600</b>	420 x 410mm, 470 x 410mm, 600 x 410mm
<b>Free airflow rating</b>	10,000mm <sup>2</sup> per running metre
<b>Colour</b>	Black
<b>Material</b>	Lightweight rigid PVCU
<b>Observations</b>	For roof pitches of 15 degrees and above



## TYPE REV

### Refurbishment Eaves Ventilator

- Black - checking of correct placement is easy
- Large protected air pocket
- High airflow 10,000mm<sup>2</sup> per metre run
- Compliance of ventilation regulations



#### Solution

The Refurbishment Eaves Ventilator fits between rafters and can be placed in position from within the attic space. The ventilator bottom portion rests under the insulation.

The ventilator top hinged portion hinges to follow the roof line. Its simple shape allows air to travel to and from the roof void. Insulation is not permitted to close the gap between the truss rafters.

#### Bill of Quantity / Specification Wording

##### 900 Eaves Ventilators

Type REV Refurbishment Eaves Ventilator by Cavity Trays of Yeovil Somerset BA22 8HU (01935 474769). Colour black. State truss centres \_\_\_\_\_mm. Fold and locate against ceiling board and roofing underlay between trusses. Number \_\_\_\_\_.

<b>Product name</b>	Type REV Refurbishment Eaves Ventilator
<b>Size (2) to suit three truss centres 400/450. 600</b>	380 x 500 x 50mm and 580 x 500 x 50mm
<b>Free airflow rating</b>	15,000mm <sup>2</sup> per running metre on all trusses
<b>Colour</b>	Black
<b>Material</b>	PVC
<b>Observations</b>	For roof pitches of 15 degrees and above

